

# NEW FORMULA!

MULTISEASON PUMPABILITY FROM +0°F to +340°F



- Heavy Load
- Water Resistant
- High Temperature
- Extreme Stability



## EXTRA ISO 460 HEAVY DUTY

# XHD CS5 GREASE

ISO 460 FORMULA

Extra Heavy Duty with 5% Moly

### CALCIUM SULFONATE GREASE

#### Characteristics\*

Ambient Range	0°F to +340° F
Ambient Range	-17° C to +171° C
Min. Pumping Temp .	0° F
Base Fluid Type	Petroleum/ Mix
Thickener Type	Calcium Sulfonate Complex
Color	Dark Gray
% Molybdenum disulfide	5
Worked Penetration (mm)	265-295
% Change/100,000 stroke	+/-5
Roll Stability w/H2O % Change	+/-5
Viscosity @ 100°C, cSt	+/- 26
Viscosity @ 40°C, cSt	+/- 460
4 Ball Wear (mm) Max, Typ.	0.5
4 Ball E.P. Weld Point (kg) Min.	620
Timken E.P. Test OK load (lb) Typ.	60
Oxidation-psi drop/500 hr Max	N/A
Rust Test	Pass
Salt Fog Test, hours	+1100
Copper Corrosion	1a
Dropping Point	+288°C (+550°F)

#### MULTI-SEASON

### Construction and Mining Grease **XHD**

#### Calcium Sulfonate Complex with 5% Molybdenum

Contains 5% moly to minimize wear on heavy duty construction equipment. Meets or exceeds the requirements for Caterpillar MPGM, John Deere , FMC, and Mack FG-C. Exceptional performance for ball joints and pin and bushing applications. recommended where high temperature and water contamination may be a concern. Will not soften when introduced to water. Superior load carrying Capabilities. For use in heavy equipment, on and off road trucks, agriculture and mining equipment.

FOR INFORMATION:

4800 Van Cleave St Indianapolis, IN 46226

## BROWN'S OIL SERVICE

- 35lb PAIL
- 120lb KEG
- 400lb DRUM

Phone: 317-545-OILS